



SPECIFICATIONS									
WIRING	INPUT		OUTPUT			SHAFT ROTATION TO INCREASE VOLTAGE	TERMINAL CONNECTIONS		
	VOLTS	HERTZ	VOLTS	MAX. AMPS	MAX. KVA		FOR INCREASING VOLTAGE AS VIEWED FROM ROTOR END		
SINGLE PHASE PARALLEL	120	50/60	0-140	100	14.0	CW	INPUT	JUMPER	OUTPUT
							1-2	---	1-B

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS #	DECIMALS	Holes	ANGLES	DRAFT	UNITS	TITLE:			
.XX	.002	.002	1°	1-1/2°	IN [mm]	SPEC. CONTROL DRAWING			
XXX	.002	.002				VARIABLE TRANSFORMER			
						TYPE: 5011-2P			
MATERIAL:	ALL DIMENSIONS APPLY AFTER PLATING		DRAWN BY		DATE	FIRST USED ON	DO NOT SCALE DWG.	CUSTOMER APPROVAL	DATE
	The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any article disclosed therein except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.		TIM RAU		4/16/97				
	CHECKER	DATE	WEIGHT APPROX.	CODE IDENT. NO.	DWG. SIZE	DWG. NO.			
	ENGINEER	DATE	SCALE	83008	D	031-6014			
			.5=1		SHEET 1 OF 1				

