



All dimensions are in mm; tolerances acc. ISO 2768 m-H

Interface

According to MIL-STD-348

Documents

Assembly instruction 19E5

Material and plating

Connector parts

Center contact
Outer contact
EMI-Ring
Dielectric

Material

Beryllium copper
Beryllium copper
Spring bronze
PTFE

Plating

AuroDur, gold plated
AuroDur, gold plated
AuroDur, gold plated

Electrical data

| | |
|---------------------------|---|
| Impedance | 50 Ω |
| Frequency | DC to 26.5 GHz |
| Return loss | ≥ 30 dB, DC to 4 GHz ≥ 23 dB, 4 to 12 GHz ≥ 20 dB, 12 to 18 GHz |
| Insertion loss | ≤ 0.1 x $\sqrt{f(\text{GHz})}$ dB, DC to 18 GHz |
| Insulation resistance | ≥ 5 GΩ |
| Center contact resistance | ≤ 6.0 mΩ |
| Outer contact resistance | ≤ 2.0 mΩ |
| Test voltage | 500 V rms |
| Working voltage | 335 V rms |
| Contact Current | 1.2A DC max. |

- Limitations are possible due to the used cable type -

Mechanical data

| | |
|----------------------------------|------------|
| Mating cycles | |
| if mating part is smooth bore | ≥ 1000 |
| if mating part is limited detent | ≥ 500 |
| if mating part is full detent | ≥ 100 |
| Center contact captivation | ≥ 7 N |
| Engagement force | |
| - smooth bore | 9 N max. |
| - limited detent | 45 N max. |
| - full detent | 68 N max. |
| Disengagement force | |
| - smooth bore | 2.2 N min. |
| - limited detent | 9 N min. |
| - full detent | 22 N min. |

Environmental data

| | |
|---------------------|--------------------------------------|
| Temperature range | -65°C to +155°C |
| Thermal shock | MIL-STD-202, Method 107, Condition B |
| Vibration | MIL-STD-202, Method 204, Condition B |
| Shock | MIL-STD-202, Method 213, Condition A |
| Moisture resistance | MIL-STD-202, Method 106 |
| RoHS | compliant |

Tooling

N/A

Suitable cables

UT 85-M17, RG 405 /U

Weight

Weight 0.22 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
|--|----------|-----------------|----------|------|--|-----------|---------------|
| Gramsamer Josef | 04/11/09 | J_Krautenbacher | 13.07.16 | c00 | 15-1629 | I_Wallner | 13.07.16 |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de | | | | | Tel.: +49 8684 18-0 email: info@rosenberger.de | | Page 2 / 2 |